



Ti-Pure TS-6200 the High Performance Exterior Advantage

Ti-Pure TS-6200 titanium dioxide is specifically designed for applications demanding high initial haze-free gloss and a high degree of gloss and tint retention over the life of the coating. (see Figure 1 and 2) Ti-Pure TS-6200 titanium dioxide delivers a unique combination of:

- Durability
- Gloss
- High Hiding Power
- Superior Dispersion

Unique Combination of Exterior Weathering and Initial Gloss Performance

Ti-Pure TS-6200 provides exterior protection by balancing weathering and gloss (see **Figure 3**). Ti-Pure TS-6200 consistently outperforms competitive super durable pigments in gloss and tint retention in a wide range of applications.

Figure 4 displays the chalk resistance of Ti-Pure[™] TS-6200 relative to traditional durable and universal grades of titanium dioxide.

Figure 1: Ti-Pure™ TS-6200 Exhibits High Initial Gloss




Figure 2: Ti-Pure TS-6200 Delivers Maximum Durability as measured by Gloss Retention




Figure 3: Ti-Pure[™] TS-6200 has Outstanding Performance — Balancing Gloss and Weathering




Figure 4: Ti-Pure[™] TS-6200—Superior Color Retention Versus Universal and Traditional Durable Pigments






Figure 5: Ti-Pure TS-6200 Disperses Easily — Saving Time and Energy

Superior Dispersion

Ti-Pure[™] TS-6200 disperses easily; saving time and energy. **Figure 5** demonstrates the alkyd ease of dispersion advantage of TS-6200 relative to competitive universal and super durable grades. It also highlights the opportunity for productivity improvements and energy savings from using Ti-Pure[™] TS-6200.

As alkyd dispersion time and intensity are increased the dispersion condition is evaluated using a special hegman gauge.


The results show a wide variation in how different ${\rm TiO_2}$ grades disperse following the various grind conditions. While most pigments require the highest grind intensity (5 minutes at 12 m/s) to achieve clean dispersion, Ti-Pure TS-6200 achieves a clean dispersion with much less time and energy.

Dispersion condition is analyzed using the Chemours™ Dispersion Optical Counter (DOC) which takes a digital image of the drawdown and uses proprietary protocol to measure the number of undispersed particles (see **Figure 6**).

High Hiding Power

Ti-Pure TS-6200 provides equivalent hiding at lower film thickness as compared to traditional durable and universal pigments. **Figure 7** demonstrates Ti-Pure TS-6200 hiding performance in a powder coating.


Figure 6: Ti-Pure TS-6200 Displays Better Dispersion



4 Times Fewer Undispersed Particles

Pigments Dispersed 15 min with a tip speed of 5.3 m/s by HSD 2" Cowles Blade, 5.3 m/s for 15 minutes $69.5\%\, \text{TiO}_2\,$ Solids as measured in a polyester coil formulation Illustrates dispersion differences as detected by the Chemours" Optical Counter


Figure 7: Ti-Pure™ TS-6200—Hiding Advantage



The High Performance Exterior Advantage

Ti-Pure TS-6200 advantage for discerning customers seeking a long-lasting coating that stands up to the test of time.

Figure 8: Ti-Pure TS-6200 — Exterior Advantage



The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.

Ti-Pure TS-6200 — Request Your Sample Today!

Ti-Pure TS-6200 titanium dioxide —the easy choice for your industrial and architectural applications. Available in 25 kg bags and 1 metric (1000 kg) tonne flexible intermediate bulk containers. If you need additional information or would like to request a sample, please visit our website or contact your local representative.

For more information, visit tipure.com